



AVO Series by ABERMAN is one of the best known model of the pendant speaker products on the market. Speakers are available in white and black colors. Housed in specially designed polypropylene high-durable body, speaker construction is robust and provides extra sound quality. Thanks to the its design and materials the AVO series are waterproof all weather speakers and comply to IP55 specification and could be used in outdoor environments. Deformation-resistant aluminum or optional steel grille protects speakers drivers from dust and external damage.

AVO speakers enforced with one low-middle range woofer driver and high frequency tweeter. This ensures in wide frequency response and perfect sound quality. Equipped with a 70/100-volt linear high quality transformer with several power taps and 8 Ohm output mode, these speakers are ideal for background music, paging system and other PA applications. More over, AVO speakers are good enough to be used for Hi-Fi tasks as well. The wide dispersion diagram ensures the best acoustic results.

The AVO series enforced with 6.5" low-mid range driver and 1" high frequency tweeter for almost full range coverage. Rated as 40W RMS and 80W maximum output power.

Each speaker comes with removable adjustable ring adapter and steel cord with hooks for Easy-and-Fast Fixing. This allows to fix speaker at desired height to achieve the best angle to cover all the needed area with high sound pressure and perfectly reproduced clear and deep sound.

Nice design is made and simple installation allows to use these speakers for many of sound reinforcement setups. Speakers used for background music, announcement and many other PA setups worldwide. Regardless to the task - commercial building or education class, conference room or house of worship, hotel lobby or park area, swimming pool or open air - the AVO series will help to add perfect sound to the beautiful views.

FEATURES

- Two-way Pendant High Efficient PA Speaker
- 40W RMS/ 80W Max Power
- 6.5" low-mid driver and 1" high frequency tweeter
- 8Ohm Input and Integrated Transformer 70/100V
- Rotary control for operating modes and power taps
- Public Address Ready System
- Body Design for high sound quality, deep bass and crisp highs
- Water-resistant driver and tweeter
- Durable ABS body and aluminum grille for drivers protection
- IP55 ratted Indoor for Outdoor usage
- Easy-and-Fast Fixing pendant accessories included
- Euroblock connection type

SPECIFICATIONS

Model	AVO62
Driver's Types	6.5"+1"
Sensitivity (1W/1m)	91dB
Frequency Response	70Hz-18kHz
RMS Power	40W
Impedance	8Ohm
70V Taps	2.5/5/10/20/40W
100V Taps	5/10/20/40W
Input Connector	Euroblock 4-pin
Ingress Rating	IP55
Body	ABS Plastic
Grill	Aluminum Alloy
Available Colours	Black / White
Mounting	Pendant (mounting accessories included)
Size (DxH)	203x285
Net Weight (kg)	3.15

ORDERING INFORMATION

Model No.	Product Description
AVO62B	Pendant Two-Way IP55 Speaker 40W, 6", Black
AVO62W	Pendant Two-Way IP55 Speaker 40W, 6", White

